

# Vertex S

BACKSHEET MONOCRYSTALLINE MODULE

PRODUCT: TSM-DE09R.B5  
PRODUCT RANGE: 405-425W

425W

MAXIMUM POWER OUTPUT

0~+5W

POSITIVE POWER TOLERANCE

21.3%

MAXIMUM EFFICIENCY



### Outstanding Visual Appearance

- Designed with aesthetics in mind
- Excellent cell color control by dedicated cell blackening treatment and machine selection.
- Thinner wires that appear all black at a distance



### Small in size, big on power

- Small form factor. Generate a huge amount of energy even in limited space.
- Up to 425W, 21.3% module efficiency with high density interconnect technology
- Multi-busbar technology for better light trapping effect, lower series resistance and improved current collection
- Reduce installation cost with higher power bin and efficiency
- Boost performance in warm weather lower temperature coefficient (-0.34%) and operating temperature



### Universal solution for residential and C&I rooftops



- Designed for compatibility with existing mainstream optimizers, inverters and mounting systems
- Perfect size and low weight. Easy for handling. Economy for transporting
- Diverse installation solutions. Flexible for system deployment



### High Reliability

- 15 year product warranty
- 25 year performance warranty with lowest degradation;
- Minimized micro-cracks with innovative non-destructive cutting technology
- Ensured PID resistance through cell process and module material control
- Mechanical performance up to 6000 Pa positive load and 4000 Pa negative load

### Trina Solar's Backsheet Performance Warranty




### Comprehensive Products and System Certificates




IEC61215/IEC61730/IEC61701/IEC62716  
ISO 9001: Quality Management System  
ISO 14001: Environmental Management System  
ISO14064: Greenhouse Gases Emissions Verification  
ISO45001: Occupational Health and Safety Management System




## DIMENSIONS OF PV MODULE(mm)



## I-V CURVES OF PV MODULE(415 W)



## P-V CURVES OF PV MODULE(415W)



## ELECTRICAL DATA (STC)

Parameter	405	410	415	420	425
Peak Power Watts - P <sub>MAX</sub> (Wp)*					
Power Tolerance - P <sub>MAX</sub> (W)			0 ~ +5		
Maximum Power Voltage - V <sub>MPP</sub> (V)	41.3	41.5	41.7	42.0	42.2
Maximum Power Current - I <sub>MPP</sub> (A)	9.82	9.87	9.94	10.01	10.08
Open Circuit Voltage - V <sub>OC</sub> (V)	49.7	49.8	50.0	50.1	50.2
Short Circuit Current - I <sub>SC</sub> (A)	10.50	10.53	10.55	10.58	10.61
Module Efficiency η <sub>m</sub> (%)	20.3	20.5	20.8	21.0	21.3

STC: Irradiance 1000W/m<sup>2</sup>, Cell Temperature 25°C, Air Mass AM1.5. \*Measuring tolerance: ±3%.

## ELECTRICAL DATA (NOCT)

Maximum Power - P <sub>MAX</sub> (Wp)	306	309	312	317	321
Maximum Power Voltage - V <sub>MPP</sub> (V)	38.3	38.5	38.7	39.2	39.5
Maximum Power Current - I <sub>MPP</sub> (A)	7.99	8.03	8.07	8.10	8.13
Open Circuit Voltage - V <sub>OC</sub> (V)	46.8	46.9	47.1	47.1	47.2
Short Circuit Current - I <sub>SC</sub> (A)	8.46	8.49	8.50	8.53	8.55

NOCT: Irradiance at 800W/m<sup>2</sup>, Ambient Temperature 20°C, Wind Speed 1m/s.

## MECHANICAL DATA

Solar Cells	Monocrystalline
No. of cells	144 cells
Module Dimensions	1762×1134×30 mm (69.37×44.65×1.18 inches)
Weight	21.8 kg (48.1 lb)
Glass	3.2 mm (0.13 inches), High Transmission, AR Coated Heat Strengthened Glass
Encapsulant material	EVA/POE
Backsheet	Black-White
Frame	30mm(1.18 inches) Anodized Aluminium Alloy
J-Box	IP 68 rated
Cables	Photovoltaic Technology Cable 4.0mm <sup>2</sup> (0.006 inches <sup>2</sup> ), Portrait: 350/280 mm(13.78/11.02 inches) Length can be customized
Connector	MC4 EV02 / TS4*

\*Please refer to regional datasheet for specified connector.

## TEMPERATURE RATINGS

NOCT (Nominal Operating Cell Temperature)	43°C (±2°C)
Temperature Coefficient of P <sub>MAX</sub>	-0.34%/°C
Temperature Coefficient of V <sub>OC</sub>	-0.25%/°C
Temperature Coefficient of I <sub>SC</sub>	0.04%/°C

## MAXIMUM RATINGS

Operational Temperature	-40~+85°C
Maximum System Voltage	1500V DC (IEC)
Max Series Fuse Rating	20A

## WARRANTY

15 year Product Workmanship Warranty  
 25 year Power Warranty  
 2% first year degradation  
 0.55% Annual Power Attenuation

(Please refer to product warranty for details)

## PACKAGING CONFIGURATION

Modules per box: 36 pieces  
 Modules per 40' container: 936 pieces